


- Low-Profile
- Aluminum Diaphragm
- NBR Rubber Surround
- Ferrite Magnet
- High Excursion




SPECIFICATIONS

Transducer Size	4.5	in	
Impedance	4	Ω	
Frequency Range ¹	90 - 4000	Hz	
Sensitivity ² (2.83V 1W @ 1m)	85.2 82.2	dB	
Power Rating (IEC 268-5)	20	W	
Voice Coil Size	25.7	mm	
Air Gap Winding Height	$H_{ag} H_{vc}$	5 11.4	mm
Net Weight	0.21	kg	

PARAMETERS ³

Eff. Piston Area	S_d	58.1	cm ²
DC Resistance	R_e	3.3	Ω
Minimum Impedance	Z_{min}	3.7	Ω
Inductance	L_e	0.344	mH
Resonance Frequency ⁴	F_s	90	Hz
Mechanical Q Factor	Q_{ms}	3.46	-
Electrical Q Factor	Q_{es}	0.772	-
Total Q Factor	Q_{ts}	0.63	-
Moving Mass	M_{ms}	8.45	g
Compliance	C_{ms}	370	$\mu\text{m}/\text{N}$
Equivalent Volume	V_{as}	1.79	L
Motor Force Factor	Bl	4.53	Tm
Motor Efficiency	β	6.15	(Bl) ² / R_e
Linear Excursion ⁵	X_{max}	4.85	mm
Max Mechanical Excursion ⁶	X_{mech}	-	mm



Details on this spec sheet are for reference only and should not be used for setting production limits. Specifications and product cosmetics are subject to change without notice. Peerless is a registered trademark of Tympany Enterprises. All measurements conducted in test lab at 25°C ±10°C, 50%RH ±10%. ¹ Specified by Engineering as linear working range of transducer. ² Measured at 2.83V at 1m and normalized to 1W with respect to nominal impedance. ³ Measured in Free Air without preconditioning, therefore subject to some deviation. ⁴ Impedance and F_s value measured under different conditions. ⁵ Equal/Overhung: $(H_{vc} - H_{ag})/2 + H_{ag}/3$. Underhung: $(H_{ag} - H_{vc})/2 + H_{vc}/3$. ⁶ Mechanically limited excursion (e.g. bottoming, spider crash).