

SUPRA RONDO 4X2.5

Twisted Loudspeaker Cable

Gauge: 4x2.5mm² / AWG 13

Rev. date: 2026-05-18

Customs tariff no: 8544499390

Country of origin: Sweden

- Twisted - Highly flexible
- Low inductance
- Double insulated, approved for 100V systems
- Tin-plated - Corrosion resistant



RONDO 4x2.5 - Versatile, flexible and possible to Star Quad wiring

High-quality speaker cable featuring four tin-plated multi-strand conductors, tightly twisted with a short pitch for optimal noise cancellation and exceptionally low inductance. The Supra Rondo cable supports several connection configurations, including full-range Star Quad, bi-wire, and bi-amplified setups. In its full-range Star Quad configuration, the conductors are arranged in a nearly ideal geometry that effectively suppresses inductance and minimizes interference. Listening tests have shown that the Star Quad configuration delivers superior musical transparency and improved signal transfer. Our advanced manufacturing process allows for extremely tight twisting while maintaining excellent flexibility and long-term durability. This makes the cable highly resistant to handling fatigue and especially suitable for demanding stage and professional audio applications. In addition to the Star Quad conductor layout, the short-pitch twisting further reduces inductance and lowers susceptibility to RFI (Radio Frequency Interference) and other high-frequency electromagnetic disturbances. Reducing RFI within hi-fi and multimedia systems contributes to a lower noise floor, enhanced clarity, sharper imaging, and improved micro-dynamics. The result is a cleaner, more detailed soundstage with deeper bass impact and greater dynamic performance emerging from a silent background.

Star Quad connection

CONSTRUCTION

Conductor (x4):	Tin-plated OFC-wire 320x0.10 mm
Diameter:	2.3 mm
Cross section Area:	4x2.5mm ² / AWG 13
Insulation:	Blue, white, black & red
Insulation thickness:	0.7 mm
Jacket:	PVC GA78, round
Jacket thickness:	1.5 mm
Diameter:.	9 mm
Colour:	Ice Blue & Anthracite grey (other colours upon request)
Marking:	SUPRA RONDO 4x2.5 + Made in Sweden + Meter mark
Weight:	155 kg/km
Packaging:	Bobbin 75m (other lengths upon request), 5m & 10m



ELECTRICAL SPECIFICATION

Resistance:	6.8 ohm/km
Inductance:	0.35 uH/m (star quad connection lower to 0.25 uH/m)
Rated voltage:	100V

PRODUCT	Qty	Part.no	EAN-13	E-no	Carton
RONDO 4X2.5 GREY B75	75M	1000000131	7330060000102	4866373	
RONDO 4X2.5 BLUE B75	75M	1000000230	7330060000201	4866343	
RONDO 4X2.5 BLUE 5M	1PC	1000000461	7330060201899		13pcs
RONDO 4X2.5 BLUE 10M	1PC	1000000594	7330060202650		13pcs