

## SUPRA XL ANNORUM XLR AUDIO


High-end Interconnect with gold-plated XLR plugs

Gauge: 1.6mm<sup>2</sup> / AWG 15 + Drain Wire

Rev. date: 2026-06-04

Customs tariff no: 8544429010

Country or origin: Sweden



- Transparent and dynamic sound
- Minimal phase shifting reactance
- Extremely low microphonic effect
- Robust & slim 24K gold-plated XLR connectors

### XL Annorum Interconnect XLR - Transparent and dynamic

XL Annorum Interconnect is a development of our popular speaker cable of the same name. It features a hybrid construction combining the XL Annorum speaker cable and Sword interconnect, taking the best from both designs. The geometry is closely related to the Sword-I, while conductor materials, damping fillers, and the rubberized outer jacket are derived from the XL Annorum speaker cable. During testing and development, we were impressed by how exceptionally quiet the cable became. The rubber-based damping material effectively protects against microphonic effects, which are typically volume-dependent and increase with level. In our tests, no audible or measurable microphony could be detected. Combined with the Sword-inspired transparency and minimal phase-shifting characteristics, the result is a high-end cable positioned at a mid-range price point.

The main difference compared to the flagship Sword-I is the use of lacquered Litz wires in Sword-I, which offers slightly higher performance but also significantly increases cost and manufacturing complexity, as each strand must be individually stripped before soldering—unnecessary for the XL Annorum Interconnect. The construction consists of two bifilar-spun conductors made from 6+6 bare 5N oxygen-free copper wires, wound in two layers around a plastic core with short pitch. This provides favourable capacitance values and effectively reduces current restriction (skin effect). Additional benefits include a tightly controlled PP insulation with high chemical stability, helping to minimise long-term conductor corrosion. The conductors are twisted together with damping filler material, effectively shielded with aluminium foil, and then embedded in a rubberised outer jacket.

Performance Characteristics: Transparent and dynamic sound, minimal phase-shifting reactance, extremely low microphonic effect, and robust, slim 24K gold-plated XLR connectors for secure contact and long-term reliability. The specification and performance sit between our flagship SUPRA Sword-I and EFF-I.

### CONSTRUCTION

Cable:	XL Annorum Interconnect
Conductors (x2):	2x6x0.40 (Bare OFC) spun around PE/PP-filler
Area:	2x1.5mm <sup>2</sup> / AWG 15
Isolation:	PP/PE mix, D=3mm
Parts:	Twisted
Screen:	Common Alu/Pet foli, 100%. Balanced, connected at both ends
Jacket:	Rubber based PVC GA54, round, D=8mm
Colour:	Ice Blue
Connectors:	<a href="#">Swift XLR</a> , 3-pin balanced connection
- Type:	Stereo, 2 XLR Female > 2 XLR Male
- Material:	Pins 24K gold plated OFC, Right = red, left = black
- Wire connection:	Soldering. Solder tin Almit 34 Super
- Jack connection:	Quick lock
Signal direction:	Female > Source > to > Male > Receiver
Packaging:	0.8M-2M: 19x23x4cm / 2+M: 31x28x4.3cm



Special length are made upon request.

PRODUCT	Qty	Part.no	EAN-13	Carton Weight
XL ANNORUM INTERCONNECT XLR 0.8M	1PAIR	1001909603	7330060208966	25 0,46
XL ANNORUM INTERCONNECT XLR 1M	1PAIR	1001909595	7330060208959	25 0,49
XL ANNORUM INTERCONNECT XLR 1.5M	1PAIR	1001909611	7330060208973	25 0,57
XL ANNORUM INTERCONNECT XLR 2M	1PAIR	1001909629	7330060208980	25 0,64
XL ANNORUM INTERCONNECT XLR 3M	1PAIR	1001910585	7330060211041	16 0,70
XL ANNORUM INTERCONNECT XLR 4M	1PAIR	1001910593	7330060211058	16 0,75